

Always Smooth, Always Ahead

PRODUCT DATA SHEET

BALMEROL MULTIPURPOSE GREASE NO. 2 & NO. 3

PRODUCT DESCRIPTION

BALMEROL MULTIPURPOSE GREASE NO. 2 & NO. 3 are superior quality lithium base greases having excellent thermal and structural stability along with excellent resistance to water. The combination of high quality base stock with synergistic blend of antioxidants, rust inhibitors, etc. make the greases suited to a wide range of usage areas. **BALMEROL MULTIPURPOSE GREASE NO. 2 & NO. 3** are available in NLGI 2 & 3 consistency ranges respectively.

TYPICAL APPLICATIONS

BALMEROL MULTIPURPOSE GREASE NO. 2 & NO. 3 are recommended for multipurpose automotive applications such as wheel bearings, chassis points, water pump bearings, machine tools as well as grease lubricated gears, couplings and universal joints. **BALMEROL MULTIPURPOSE GREASE NO. 2** is pumpable and can be dispensed by centralised greasing systems. **BALMEROL MULTIPURPOSE GREASE & NO. 3** is recommended for wheel bearings due to its excellent resistance to shearing while **BALMEROL MULTIPURPOSE GREASE NO. 2** is recommended for all general grease lubrication areas.

AVAILABILITY

BALMEROL MULTIPURPOSE GREASE NO. 2 & NO. 3 are available in 180 kg and 18 kg.



Always Smooth, Always Ahead

BALMEROL MULTIPURPOSE GREASE NO. 2 & NO. 3

TECHNICAL DATA

Sl. No.	Characteristics	MULTIPURPOSE GREASE NO. 2	MULTIPURPOSE GREASE NO. 3	Test Method
1.	Soap type	Lithium	Lithium	
2.	Texture	Smooth	Smooth	
3.	Worked penetration at 25°C	265-295	220-250	ASTM D 217
4.	Base oil viscosity @ 40°C	90-110	90-110	ASTM D 445
5.	Drop point, °C, min.	180	180	ASTM D 566
6.	Oxidation stability at 99°C, 100 hrs, drop in pressure, kgf/cm ² , max.	0.50	0.50	ASTM D 942

